

## Product Data Sheet

Revised: 2020/01/22 (version 4.1)



# PETRONAS Arbor Multi FCT 10W-30

## For Tireless Machinery, The Best Fluid Technology for Your Daily Work

For all the agricultural and construction equipment hard workers, machineries are the lifeblood of their business. Ensuring that they are always working tirelessly and efficiently is the Number One priority. Machinery need the best fluid technology to last longer while working, especially when operating under severe conditions.

### Description and Applications

PETRONAS Arbor Multi FCT 10W-30 is a premium transmission oil (U.T.T.O.) dedicated to agricultural and construction machinery, able to keep their efficiency and offering a longer. Perfect solution for high and long-lasting performances for your hard-daily work, protecting your tireless machinery from loss of performances and unplanned downtimes.

PETRONAS Arbor Multi FCT 10W-30 is suitable for transmissions, final drives, hydraulic systems and wet brakes of farm tractors and machineries. Also suitable for SDFG tractors.

### Benefits

PETRONAS Arbor Multi FCT 10W-30 enhances your Business Profits and your vehicle availability while significantly reducing your operating costs through:

- **High anti-wear properties** of the mechanical components of the transmission and hydraulic system
- Excellent capability to keep transmission and hydraulic systems clean from deposits and sludge
- Improved friction materials durability

Provides outstanding Working Experience through:

- **Enhanced noise reduction** of friction materials (clutches and wet brakes)
- **High braking efficiency** deriving from the presence of balanced friction modifiers
- **Prompt response of the servcontrols** of the hydraulic circuit ensured by the viscometric stability to changes in temperatures that determines a high and constant pressure in the system
- Excellent low temperature viscosity for improved lubrication during start-up

### Approvals, Specifications and Recommendations

#### Specifications:

- API GL-4

#### Performance Level:

- SDFG OT-1891A

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

## Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm <sup>3</sup>	0,890
Kinematic Viscosity @100°C	ASTM D 445	mm <sup>2</sup> /s (cSt)	11,2
Viscosity Index	ASTM D 2270	-	160
Flash Point COC	ASTM D 92	°C	195
CCS at -25°C	ASTM D5293	mPa·s (cP)	6600
Pour Point	ASTM D 97	°C	-30

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

### Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: [www.pli-petronas.com](http://www.pli-petronas.com)

### Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 76777