



IMB 164

New Product Release Document

Marketing Department.

July 08, 2022

This document is created to register the marketing communication collaterals and process details for the launch of the above-mentioned pattern; it is intended for internal circulation and approval for further dissemination. All facts and figures mentioned in the document is true to the best of our knowledge as on the above said date, for updated information please feel free to visit the website www.ascensotyres.com

New Product Release Document

Release Month: July'22

Brand: ASCENSO

Tread Pattern : IMB 164

Tyre Construction: Bias

Type: Tube Less/Tube Tyre

Main Applications: Implements

TRA Code : IMP

List of Sizes

Size	LSI
200/60-14.5	10
200/60-14.5	14
250/65-14.5	12



Salient Features

Specially Designed Rib Tread Pattern:

- Ensures soil protection
- Suitable for both On Road and Off-Road applications
- Built for carrying high loads



Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)			
								Speed, km/h (mph)			
		SW	OD					Mixed application			
		mm	mm					10	25	30	40
		in	in					bar	psi	6	16
200/60-14.5	AG 6.75	205 8.07	608 23.94	283 11.14	1818 71.57	10PR 106 A8	3.7	1110	940	880	790
							54	2442	2068	1936	1738
							4.1	1180	1000	940	840
							59	2596	2200	2068	1848
							4.5	1250	1060	1000	890
							65	2750	2332	2200	1958
							5	1330	1130	1060	950
							73	2926	2486	2332	2090
						14PR 113 A8	5.2	1360	1150	1090	970
							75	2992	2530	2398	2134
							5.7	1430	1210	1140	1020
							83	3146	2662	2508	2244
							6.3	1510	1290	1210	1080
							91	3322	2838	2662	2376
7	1610	1370	1290	1150							
102	3542	3014	2838	2530							

Note:All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)			
								Speed, km/h (mph)			
		SW	OD					Mixed application			
		mm	mm					10	25	30	40
		in	in					6	16	20	25
250/65-14.5	AG 8.00	251 9.88	694 27.32	318 12.52	2076 81.73	12PR 119 A8	3.6	1620	1380	1300	1160
							52	3564	3036	2860	2552
							3.9	1710	1450	1370	1220
							57	3762	3190	3014	2684
							4.3	1810	1540	1440	1290
							62	3982	3388	3168	2838
							4.7	1900	1620	1520	1360
							68	4180	3564	3344	2992

Note: All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover