

PRODUCT DATA SHEET

PEB 723

Tyre Construction: Bias

Type: Tube Less

Main Applications: Reach Stacker

TRA Code: L4-S



Salient Features:

Flat Tread with Larger width:

Offers better stability and easy maneuvering for applications like reach stackers and empty container handlers.

Reinforced Sidewall:

Resistance to damage.

Specially Formulated Tread Compound:

Improved heat resistance, Quick heat dissipation and cooler running on hard concrete surfaces.

Strong Casing/Carcass with Special Compound:

Used in Heavy duty applications.



Technical Data



Size	Recomm. Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load (kg) (lbs)	
		SW	OD					Speed (kmph) (mph)	
		mm	mm				mm	mm	Bar
18.00-25	13.00/2.5	inch	inch	inch	inch	psi	6	16	
		528	1650	736	4935	10.3	22950	21250	
		20.8	65	29	194.3	150	50600	46860	

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com